

| | |
|--------------------------|----------------------------|
| Luminous Flux (Lumen) | 4320 |
| Luminous Efficacy (lm/W) | 130 |
| IP-rating | IP40 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection | Screwless terminal, 5-Pole |
| Finish of Reflector | Frosted |
| Power factor | >0.90 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|--------------------------------|
| Mounting Method | Recessed |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PS (Polystyrene) |
| Operating Temperature | -10 to +50 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | White |
| Housing | Aluminium |
| Colour of material | White |

Dimensions

| | |
|----------------|-------------|
| LED panel size | 62.5x62.5cm |
| Length (mm) | 620 |
| Width (mm) | 620 |
| Height (mm) | 32 |

Why Any-lamp?



Order from the **largest lighting specialist** in Europe



Customised quotation

Sensor Information



Up to **7 years warranty**



Easy return process

| | |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|